




VACUUM AND STEAMING IRONING BOARD

Series 3000



Universal ironing board with steaming and vacuum.

- Steam heated ironing surface.
- Garment holders.
- 4-layer padding with pure silicon foam. Silicon iron rest.
- High-depression vacuum motor at 0,37KW - 0,5 HP
- Anti-heat buffer.

Options:

- Stainless steel swing arm with ergonomic moulding
- Electrically heated arm forms. Wide range of bucks available
- Special arm bucks upon request
- Lighting device and iron trolley
- Condensation separator group, with electric-steam or steam iron, or with temperature control using high-precision electronic display
- Anti-shine shoe in PTFE-aluminium or stainless steel
- Air-water spray gun. Steam or air/steam gun unit
- Stain removing buck in stainless steel
- Built-in electric steam generator, meeting PED approval, with capacity of 8 or 16,5 litres
- No delay in switching from vacuum to blowing, thanks to action of pneumatic cylinders.




Made in Italy with Italian Fashion Mind



**CARATTERISTICHE TECNICHE
TECHNICAL FEATURES**


PARAMETER		3000	3008 (Boiler 8 Lt.)	3032 (Boiler 16,5 Lt.)	3016 (Boiler 16,5 Lt.)
Supply voltage	-	230 V / 1 / 50 Hz	400 V / 3 / 50 Hz		
Ironing unit resistance	Kw	1,1			
Boiler resistance	Kw	-	6,5	6 + 9 Double switch	7,5
Vacuum unit motor	Kw	0,37			
Pump motor	Kw	-	0,5		
Water inlet	Ø	-	12mm		
Boiler discharge	Ø	-	3/4"		
Air discharge	Ø	100 mm			
Steam pressure	bar	4,5			
Net weight	Kg	120	140	150	147
Gross weight	Kg	135	155	165	162
MISURE D'INGOMBRO OVERALL DIMENSIONS					
Width	mm	1700			
Depth	mm	650			
Height	mm	900			
Different voltage and frequency specifications on request					

MAIN BUCK TABLES (MM)



ASSEMBLY AND PREPARATION OF THE MACHINE

DESCRIPTION	mm	mm	DIMENSION
WATER INLET	A1 170	A2 85	3/4"
ELECTRIC POWER	B1 585	B2 380	
CONDENSATION RETURN	C1 430	C2 60	3/8"
AIR EXHAUST	E1 745	E2 310	D.100
STEAM	F1 790	C2 60	3/8"
BOILER DISCHARGE	G1 80	E2 310	1/2"



ROTONDI group Srl
Via Fratelli Rosselli, 14/16
20019 Settimo Milanese (Milano) - Italia
Tel. (+39) 02.335.01.224 - Fax (+39) 02.335.01.329
E-mail: rotondi@rotondigroup.it
www.rotondigroup.com

Agente: