



# INDUSTRIAL TUMBLE DRYER SERIES RGS-RGB



 **ROTONDI**<sup>®</sup> group  
*A step ahead*



Made in Italy with Italian Fashion Mind



## Main characteristics:

The ROTONDI tumble dryer series is suitable for small , medium and large industrial use and was born from a technical project which aims to optimize the drying garment operation in a homogeneous way .

The systems is based on the perfect circulation of heated air combined with an effective circulation inside the structure .

Inside the completely perforated drum , the garment are keep in constant movement , enabling the air flow to be channeled in a uniform way and to remove the humidity excess .

The air expulsion it takes place through a filtering box .

Technical specification :

- air heating by lamellar heat exchangers with extractable filtering grill
- the exchangers are positioned in the upper part of the machine where the air is cleaner and warmer
- air expulsion from the bottom
- control panel to set time and temperature
- Door opening available in manual , vertical or pneumatic version

Technical data		RGS 90	RGS 135	RGB 200	RGB 260	RGB 300	RGB 320
<b>Basket diam.</b>	<b>mm</b>	1500	1500	1600	1800	1800	1800
<b>Basket deep</b>	<b>mm</b>	1100	1500	1945	2000	2250	2450
<b>Basket volume</b>	<b>lt</b>	1950	2648	3908	5086	5722	6231
<b>Load capacity Ratio1/20</b>	<b>kg</b>	97	132	200	254	290	315
<b>Loading door</b>	<b>mm</b>	1000	1000	1000	1300	1300	1300
<b>Steam inlet</b>	<b>inch</b>	1 ¼ "	1 ¼ "	1 ½ "	2 "	2 "	2 "
<b>Steam condensation</b>	<b>inch</b>	1 "	1 "	1 "	1 ¼ "	1 ¼ "	1 ¼ "
<b>Steam consumption</b>	<b>kg/h</b>	200	250	350	500	600	660
<b>Basket speed</b>	<b>rpm</b>	25	25	25	22	22	22
<b>Max. air pressure</b>	<b>bar</b>	6	6	6	6	6	6
<b>Max. steam pressure</b>	<b>bar</b>	8	10	10	10	10	10
<b>Electric power</b>	<b>kW</b>	4,7	5,2	8,8	12	12	16
<b>Electric motor power</b>	<b>kW</b>	2,2	2,2	3	4,4	4,4	6
<b>Height</b>	<b>mm</b>	2415	2900	2950	3100	3100	3100
<b>Width</b>	<b>mm</b>	1750	2000	2300	2700	2700	2700
<b>Depth</b>	<b>mm</b>	2100	2250	2850	2500	2800	3100
<b>Weight</b>	<b>kg</b>	1450	1900	2200	3500	3800	5000

P.S. Steam and water consumption are always to be checked depending on the customer needs and central supply installations .

## Options:

- Single or double tilting
- Double passing door
- Control production printed ( for double passing door type only )
- Humidity control
- Variable speed
- Automatic loading and unloading system
- Axial air circulation device



**ROTONDI group Srl**  
Via Fratelli Rosselli, 14/16  
20019 Settimo Milanese (Milano) - Italia  
Tel. (+39) 02.335.01.224 - Fax (+39) 02.335.01.329  
E-mail: rotondi@rotondigroup.it  
www.rotondigroup.com

Agente: